



The new degree of comfort.™

SUBMITTAL COVER SHEET

PROJECT NAME _____
LOCATION _____
ARCHITECT _____
ENGINEER _____
CONTRACTOR _____
SUBMITTED BY _____ DATE _____

UNIT SUMMARY

Quantity						
Unit Designation						
Model No.						
Total Cooling						
Sensible Cooling						
Air Ent. Evaporator						
Air Lvg. Evaporator						
Heating Input						
Heating Output						
CFM/ESP						
EER/SEER						
Electrical						
Minimum Ampacity						
Min.-Max. Breaker						
Net Unit Weight						
Accessory						
Catalog Form Number						

ACCESSORIES:

NOTES:



INTEGRATED HOME COMFORT

PRINTED IN U.S.A 01/12 QG FORM NO. M11-1640

SUBMITTAL SHEET FOR HIGHBOY & LOWBOY OIL FURNACES WITH PSC/DIRECT DRIVE MOTOR

ROCA-*P: Highboy Series**

ROLA-*P: Lowboy Series**

Input Ratio from 84,000 to 175,000 BTU/HR [24.61 to 51.28 kW]

JOB NAME _____ MODEL NO. _____
 CONTRACTOR _____ OUTDOOR UNIT MODEL NO. _____
 ENGINEER _____ LOCATION _____
 SUBMITTED FOR ☐ APPROVAL ☐ RECORD ORDER NO. _____
 DATE _____

UNIT DATA

HEATING PERFORMANCE

TOTAL CAPACITY INPUT* MBH [kW]
 TOTAL CAPACITY OUTPUT* .. MBH [kW]
 DESIGN TEMP. RISE °F [°C] DB
 AFUE %
 CALIFORNIA SEASONAL
 EFFICIENCY %
 (*uses blower motor heat)

SUPPLY AIR BLOWER PERFORMANCE

TOTAL AIR SUPPLY CFM [L/s]
 TOTAL RESISTANCE EXTERNAL
 TO UNIT IWG
 BLOWER SPEED RPM
 POWER OUTPUT REQUIREMENT .. BHP
 MOTOR RATING HP [W]
 POWER INPUT REQUIREMENT kW


ELECTRICAL DATA

POWER SUPPLY Hz
 TOTAL UNIT AMPACITY AMPS
 MINIMUM WIRE SIZE AWG
 MAXIMUM OVERCURRENT DEVICE
 FUSES/HACR BREAKER AMPS


FEATURES FOR ROCA/ROLA

The Rheem *Classic Series*® upflow oil furnace is for installation in properly ventilated utility rooms, closets or alcoves.


- Direct Drive blower assemblies for heating and air conditioning applications
- 10-gauge primary and 14-gauge secondary heat exchanger
- Front cleanout ports extend through front wall for accessibility
- Efficiencies up to 85.9%
- Front or rear flue Lowboy available
- All furnaces have standard Honeywell controls
- Available with Beckett, Riello Carlin burners
- Extended vestibule on all units



DIMENSIONS



**ROLA (Lowboy)
MODELS**



**ROCA (Highboy)
MODELS**

DIMENSIONS

Model	Lowboy ¹					Highboy				
	ROLA-070P			ROLA-115P		ROCA-070P			ROCA-115P	
Cabinet Height (A)	40	40	40	46	46	53-5/8	53-5/8	53-5/8	56-1/2	56-1/2
Cabinet Width (B)	20-1/4	20-1/4	20-1/4	25-1/8	25-1/8	22-1/4	22-1/4	22-1/4	25-1/2	25-1/2
Cabinet Depth (C)	47-1/2	47-1/2	47-1/2	53-5/8	53-5/8	33-1/8	33-1/8	33-1/8	38	38
Centerline Flue to Floor (D)	31-1/4	31-1/4	31-1/4	38-1/2	38-1/2	49-1/8	49-1/8	49-1/8	52-5/8	52-5/8
Centerline Flue to Side (E)	10-1/8	10-1/8	10-1/8	12-1/2	12-1/2	11-1/8	11-1/8	11-1/8	12-3/4	12-3/4
Warm Air Supply Depth (G)	17-1/2	17-1/2	17-1/2	21-1/2	21-1/2	19-3/4	19-3/4	19-3/4	23-3/8	23-3/8
Warm Air Supply Width (Ho)	18-1/4	18-1/4	18-1/4	22-7/8	22-7/8	20-1/2	20-1/2	20-1/2	23-3/4	23-3/4
Return Air Supply Width (Hr)	18-1/4	18-1/4	18-1/4	22-7/8	22-7/8	15	15	15	15	15
Return Air Supply Depth (J)	14	14	14	13-5/8	13-5/8	23-5/8	23-5/8	23-5/8	23-5/8	23-5/8
Shipping Wt.	323	323	323	362	362	298	298	298	347	347

1. Specify front or rear flue on Lowboy models.

[] Designates Metric Conversions

Before proceeding with installation, refer to installation instructions packaged with each model, as well as complying with all Federal, State, Provincial, and Local codes, regulations, and practices.

Rheem Sales Company, Inc.
P.O. Box 17010, Fort Smith, AR 72917

"In keeping with its policy of continuous progress and product improvement, Manufacturer reserves the right to make changes without notice."